



E 1/4 Cor. Sec. 25, T27S, R1W
 Thimble at corner
 1. Chiseled "X" Top of Curb 67.39' NE
 2. Chiseled "X" Top of Curb 65.75' SE
 3. Chiseled "X" Top of Curb 89.56' SW
 4. Chiseled "X" Top of Curb 86.71' NW
 5. N=1680996.41, E=1639248.71

P.I. Sta. 7+32.36 (Bk.)=
 P.I. Sta. 7+32.01 (Ahead)
 $\Delta = 12^{\circ}10'34''$
 $T = 46.36'$
 $R = 434.65'$
 $L = 92.37'$
 $E = 2.47'$
 N. C.

Sta. 8+60.98 Dondlinger Const.
 Curb Inlet (Type 1A), 22.67' Rt.
 $L=6'-4"$, $W=4'-4"$
 Inlet Top = 109.57
 See Sht. No. 15 & 27

LEGEND

Drive, Pavement and/or Sidewalk Removal

Install 2-6" PVC (Sch. 40) Irrigation Sleeves, 2.5' apart extending 2' beyond Back of Curb

MCCORMICK AVENUE STREET IMPROVEMENTS
PROJECT NAME

DONDLINGER DRIVE - STA. 6+50 TO STA. 10+00
SHEET TITLE

JRA DESIGN BY. WNJ DRAWN BY. JRA CHECKED BY.
 AUGUST 2005 DATE 03245 JOB NO. 11 / 111 SHEET/OF

411 N. WEBB ROAD
WICHITA, KS. 67204
316 - 694 - 9600