STATE OF KANSAS
STATE HIGHWAY COMMISSION
SEDGWICK COUNTY

PLAN AND PROFILE



INDEX OF SHEETS

Sheet No.1 Title Sheet
Sheet No.2 Topography
Sheet No.3 Plan & Profile
Sheet No.4 Construction Layout
Sheet No.5 General Details
Sheet No.6 Auxiliary Details
Sheet No.7 Reinforcing Detail
Sheet No.8 Piling Detail





BRIDGE ONLY

Scale 2"=1 Mile

PLANS PREPARED BY.

Rufus Kirk
COUNTY ENGINEER
DATE April 20 1933

APPROVED.

COUNTY COMMISSIONER
DATE.

CONVENTIONAL SIGNS

COUNTY LINE
SECTION LINE
WIRE FENCE
HEDGE ROW
RAILROAD
SURVEY LINE
RIGHT OF WAY
TELEPHONE
POWER POLE
TRAVELED WAY
CITY LIMITS
TOWNSHIP BOUNDRY

GROSS LENGTH OF PROJECT	532.75 FT.	0.100 9	MILES
EXCEPTIONS			
ADDITIONS			
NET LENGTH OF PROJECT	532.75 FT.	0.100 9	MILES
NET LENGTH OF BRIDGES	532.75 FT.	0.100 9	MILES
NET LENGTH OF ROAD	FT.		MILES

RECOMMENDED FOR APPROVAL DATE

ENGINEER OF SECONDARY ROADS
STATE HIGHWAY COMMISSION OF KANSAS

APPROVED DATE

STATE HIGHWAY ENGINEER
STATE HIGHWAY COMMISSION OF KANSAS

RECOMMENDED FOR APPROVAL DATE

DISTRICT ENGINEER
PUBLIC ROADS ADMINISTRATION
FEDERAL WORKS AGENCY

APPROVED DATE

DIVISION ENGINEER
PUBLIC ROADS ADMINISTRATION
FEDERAL WORKS AGENCY

112



CONTOUR MAP OF BIG DITCH AT MACARTHUR ROAD BETWEEN SECT'S. 11 & 14 T28S - R1W.

SEDGWICK COUNTY ENGINEERING DEPT.
RUFUS S. KIRK, COUNTY ENGR.

Drawn by

By Reproduction From C1121-184 U.S. Army. January 1953

Sta 0+00
S.W. Cor. Sec. 11 - Twp 28 S - R 1 W
Iron Pin
500' N. E. to Conc. Wit.
50.0' N. W. " " "
50.0' S. E. " " "
32.9' S. W. to X on W. Hdgd. RCB.
35.2' S. E. " " " E. " "

Curve Data #1
P.C. Sta 61+37.08 (See Eq.)
Δ 16°33'
D 7°00'
T 119.36'
R 819.00'
L 236.90'

Curve Data #2
P.C. Sta 9+40.58
Δ 29°04'
D 7°00'
T 212.32'
R 819.00'
L 415.24'

Sec. 11 - Twp 28 S - R 1 W

Approximate ℄ County Road Detour.

Pasture

Shelter Belt

Road No. 813

R/W 40' ℄

Road No. 813

Black Top

Farmyard

Sta 62+23 Ex. R/W

EQUATION
Sta. 5+37.09 AHEAD =
Sta. 6+36.74 BACK.

Wheat

Pasture

Sec. Easement

℄ Channel

Road Control R/W

48" C.M.P. to be furnished, installed, and removed by SEDGWICK COUNTY. ℄ to match ℄ channel "B"

Sta. 24+10 16°30' Lt. Skew
36"x 76' RCP to be furnished & installed by SEDG Co.
D.A. 30 Ac.
T.E. EL. 1285.60

Sta 23+87
16 12' x 2.8' W.P.B. (Remove)

Temporary Easement

Shelter Belt to be removed.

Shelter Belt

Dist. from ¼ Cor. to P.I. is 941.57' on Sec. line.

R/W 30' ℄

Halstead

℄ Elev. 1289.78

Sta. 2 G 1 61.5 on Sec. Line
S ¼ Cor. Sec 11 - Twp. 28 S - R 1 W
Stone 15" dia. p (24" dia. buried)
50.0' N.E. to Conc. Wit.
40.0' S. " " "
40.0' N. " " "
50.5' W. to ℄ of RR tracks

RR Sign

Pasture

Wheat

9" Graded Rock 2' Heavy Riprap to be installed by SEDGWICK COUNTY.

Limits of Borrow to channel grade, by SEDG. COUNTY.

Sec. 14 - Twp 28 S - R 1 W

Sta. 16+69.00 Construct 30'-5" 13 @ 36' 30'-5" C.C.B.

SCALES
Plan Long. 1"=100' Lat. 1"=100'
Profile Horiz. 1"=100' Vert. 1"=10'
0 50 100 200 300 400

Curve Data #3
P.C. Sta 13+82.18
Δ 29°04'
D 7°00'
T 212.32'
R 819.00'
L 415.24'

On Sec Line Sta 25+19.1 No. Pacific
On Alignment Sta 28+12

Curve Data #4
P.C. Sta 24+64.45
Δ 16°34'
D 7°00'
T 119.24'
R 819.00'
L 236.87'

B.M. #1 60' in HLP 45' SW of S.W. Cor. Sec. 11 - Twp 28 S - R 1 W Elev. ~1309.08

B.M. #2 - USGS - Con E. hdwl of RCBC 21' NE 200' Ed S ¼ Cor Sec 11 Twp 28 S - R 1 W Elev. ~1287.29

GENERAL NOTES

All easements, channel changes, borrow pit locations & R/W for construction of this project to be furnished by SEDGWICK COUNTY.

All encroachments, such as fences, telegraph, telephone and power lines, shall be moved beyond the limits of construction by owners or by SEDGWICK COUNTY.

All Stop, Curve & Directional signs to be installed by SEDGWICK COUNTY.

In the interest of public safety, all gas, gasoline oil, and water lines shall be moved beyond the limits of the roadbed unless special provision for their retention has been noted. Operational devices for any and all lines, which are permitted to remain in place, shall be adjusted to conform with line and grade of proposed improvement.

Grading & surfacing is to be done by SEDGWICK COUNTY and is not to be considered as a part of this project.

Existing embankment to be removed to natural ground level.

℄ 1280.01

℄ 1285.38

Rt 1285.00

0+00 1 2 3 4 5+00 6 7 8 9 10+00 11 12 13 14 15+00 16 17 18 19 20+00 21 22 23 24 25+00 26

PLATE 1 - PLAN-PROFILE OF R.B. & C. STANDARD



ELEVATION
Scale 1"=20'

FLOODWAY DATA

Top of Levee "C" elevation 1299.05
Top of Levee "D" elevation 1300.05
Bottom of channel elevation 1280.01
Highwater elevation 1289.09
Width of channel at bottom 260'
Side slopes of channel 1 on 2.5
Side slopes of Levees 1 on 3
Width of Roadway ctr. to ctr. of Levee 554'
Estimated Flow 45,000 c.f.s.
Estimated velocity 7.30 ft. per sec.

GENERAL NOTES

Design: According to A.A.S.H.O. Specifications, Edition of 1949 "H 20-44 Loading; f_c = 20,000 psi.; E_c = 1,000 psi.

Soundings: Taken by SEDGWICK COUNTY with ¾" jet.

Piling: Concrete piling to be driven to a computed resistance of 28 tons per pile.

Concrete: Use Class A(AE) concrete thruout. Bevel all exposed edges with a ¾" triangular molding.

Forms: Contractor shall use preformed metal forms owned by SEDGWICK COUNTY.

Embankment: To be constructed by SEDGWICK COUNTY or others. No earthwork is to be considered a part of this project except at pier locations in channelway.

GENERAL CONSTRUCTION NOTES

Timber cribbing at centerline of each span on this project will be required.

One set of short forms and four sets of long forms are available for this project. Since the concrete in a full span ahead of any forms to be removed must have attained its design strength before removal of these forms, it is suggested that high-early strength cement be used.

Forms for this project shall be picked up by Contractor at the SEDGWICK COUNTY Yards, 1015 Stillwell, Wichita, and returned to this location unless otherwise instructed by the Engineer. (See "Special Provisions" in Specifications & Proposal Booklet.)

Since the speed and simplicity of this project will be greatly increased if construction is well underway before the waterway and levees are constructed, work on forming of piling must start within two weeks and pile driving must start within three weeks after the contract is let.

A trench 5'x4'x28' to be excavated before setting piling and backfilled before any form work for caps proceeds at each pier location in channelway. Excavation and backfilling not to be paid for directly, but shall be included in the unit price bid for concrete piling.

CONSTRUCTION LAYOUT
BRIDGE NO. 628-23-1669

PREPARED BY
SEDGWICK COUNTY ENGINEERING DEPT.
RUFUS S. KIRK — COUNTY ENGINEER

REVISED	SCALE	DESIGNED	TRACED	CHECKED	SHEET NO.
	1"=20'	FREUND	FREUND		4
	DATE		4-53		
	PLANFILE		TOTAL SHEETS 8		

GENERAL NOTES

Design: Designed for H-20-44 loading AASHO specifications. f_s = 20,000 psi, f'_c = 4,000 psi.
Soundings: To be taken by Sedgwick County.
Piling: Concrete piling to be driven to a Calculated resistance of 28 ton.
Old Struct: To be removed by Sedgwick County.
Concrete: Class A(AE) concrete used throughout. Bevel all exposed edges with a $\frac{3}{4}$" Δ molding unless otherwise noted. Forms shall be preformed steel "pans" used as directed by the Engineer in charge.
Guardrail: To be of standard Barrier beam or concrete as shown on Construction Layout. Concrete rail to be constructed after the removal of deck forms



PLAN VIEW



SUMMARY OF QUANTITIES
Concrete Handrail

One End Span & Abut. — Class A(AE) Conc. 1.8 cu.yd.

Bar	Size	Length	No.
RA	16' 1	60'0"	8
RB	-	19'0"	8
RD	-	6'4"	8
DB	-	2'-8"	90

Total Weight 573 lb.

One Int Span — Class A(AE) Conc 1.8 cu.yd.

Bar	Size	Length	No.
CC	16' 4	11'8"	29
FA	16' 1	21'0"	90

Total Weight 852 lb.

SUMMARY OF QUANTITIES
(ONE GUARDRAIL POST)

Class A(AE) Conc. 0.056 CY.

Bar	No.	Size	Length	Total Wt.
PB	3	4	5'-8"	114 lb.



STANDARD G'DRL. POST DETAIL
as Required



SECTION AA



SECTION BB

Note: PA bars to be placed immediately after slab screeding

RE. CONC. MODIFIED T-BEAM BRIDGE

BRIDGE NO. 628-23-1669

PREPARED BY
SEDGWICK COUNTY ENGINEERING DEPT.
RUFUS S. KIRK — COUNTY ENGINEER

REVISED 1-15 M.J. 4-53 N.L.F.	SCALE	DESIGNED	TRACED	CHECKED	SHEET NO.
	1/4" = 1'	R.R.J.	C.D.H.		5
	DATE	9-50	9-18-50		
	PLANFILE		TOTAL SHEETS	8	



Section At Pier Type A
Use at Pier No's.

TABLE of ELEVATIONS

El A	1295.46
El B	1295.14
El C	———
Length of piling =	?

*See Construction Layout

	Type	A Abut	A Piers
2 Span Bridge	2	1	
3 " "	2	1	2
4 " "	2	3	
5 " "	2	2	2

GENERAL NOTES

Bevel all exposed edges with ¾" molding

Paint: All parts of the Metal Handrail shall receive one shop coat of red lead paint. All exposed surfaces of Structural Steel, Bearing Devices and Metal Handrail shall receive one coat of tinted aluminum paint followed by one coat of aluminum paint after erection.

Reinforcing Steel

Note: Quantities shown on this sheet are for computation only. Actual structure quantities are shown on following Sheet.

27'-7" Rdwy ABUTMENT QUANTITIES

A TYPE	B TYPE
backwall boards	backwall boards
Five bearing piling	Five bearing piling
~~Eight sheet piling~~	Eight Sheet piling
6.3 cu yd concrete	7.8 cu yd concrete
799 lbs reinforcing	579 lbs reinforcing steel
Five bearing devices	Five bearing plates
One bent plate	One bent plate

Bar	No	Length	Size	Bar	No	Length	Size
Aa	41	4'-8"	½" ø	Aa	41	4'-0"	½" ø
Ar	5	27'-0"	"	Ar	5	27'-0"	"
Ba	14	9'-8"	"	Ba	14	9'-8"	"
Ca	4	27'-0"	1" ø	Ca	4	27'-0"	1" ø

27'-7" Rdwy PIER QUANTITIES

A TYPE	B TYPE
Five bearing piling	Five bearing piling
4.1 cu yd concrete	4.1 cu yd concrete
360 lbs reinforcing steel	397 lbs reinforcing steel
5 bearing devices	
One bent plate	

Bar	No	Length	Size	Bar	No	Length	Size
Ac	14	11'-8"	½" ø	Ac	14	11'-8"	½" ø
Ca	4	27'-0"	1" ø	Ca	4	27'-0"	1" ø

27'-7" Rdwy. SPAN QUANITITIES*

ONE END SPAN	ONE INT SPAN
36.4 cu yd Conc.	37.6 cu yd conc.
8590 lbs. reinforcing steel	8868 lbs reinforcing steel
10 h rail posts (steel)	12 hand rail posts
72' Barrier beam	72' Barrier beam
1-expansion device	
2 Concrete Posts	

Bar	No	Length	Size	Bar	No	Length	Size
SA	83	5'-2"	½" ø	SA	92	5'-2"	½" ø
SB	332	5'-2"	"	SB	368	5'-2"	"
Fb	20	23'-6"	1" ø	Db	20	23'-0"	⅝" ø
				Eb	20	38'-4"	1" ø
Eb	20	33'-4"	1" ø	Fb	2	22'-0"	½" ø
Ab	2	25'-0"	½" ø	Kb	12	0'-11"	¾" ø
Bf	59	27'-0"	"	Af	66	27'-0"	"
Af	9	33'-0"	"	Bf	9	33'-0"	"
Kb	10	0'-11"	¾" ø	Cb	18	38'-0"	⅝" ø
Cb	18	33'-0"	⅝" ø	Bb	18	14'-0"	"
Bb	9	14'-0"	"	thrd	6	28'-0"	¾" ø
thrd	5	23'-0"	¾" ø	Ga	20	18'-0"	⅝" ø

* Due to overlapping & duplication quantities shown are not necessarily actual bar numbers but are factors to be multiplied by the number of each span involved to give total structure quantities
† Multiply by number of piers.



Section At Mid-Span

Bearing ℞ Detail
Place on ℄ ctrs. over pile
Use on B type Abut.



Section At Abut. Type B
Use at Abut. No's.



Note: All dimensions & Steel in these sections are identical with those in pier type A & abut type A except those shown

Section Pier Type B
Use at Pier No's.

TABLE of PIERS & ABUTMENTS

	Ac	Aa	Ab	Ba	Bb	Ca	Cb	Ga	Eb	Fb	Ka	Kb	Ab	Bf	Af	Ar	Thrd	Rdwy
Abut A	14	41	2	14	9	4	18	4	2	2	2	10	2	9	66	5	6	1
Pier A	14	41	2	14	9	4	18	4	2	2	2	10	2	9	66	5	6	1
Abut B	14	41	2	14	9	4	18	4	2	2	2	10	2	9	66	5	6	1
Pier B	14	41	2	14	9	4	18	4	2	2	2	10	2	9	66	5	6	1
Abut C	14	41	2	14	9	4	18	4	2	2	2	10	2	9	66	5	6	1



ROCKER DETAIL
40 Required







Sections of Abut Type A Use at Abut. No's.







RE CONC. MODIFIED T-BEAM BRIDGE AUXILIARY DETAILS BRIDGE NO. 628-23-1669

PREPARED BY
SEDGWICK COUNTY ENGINEERING DEPT.
RUFUS S. KIRK — COUNTY ENGINEER

REVISED	SCALE	DESIGNED	TRACED	CHECKED	SHEET NO.
12-51 M.S 4-53 W.H.K	1/2" = 1'	R. R. J.	C. D. H.		6
	DATE	9-50	9-23-50		
	PLANFILE		TOTAL SHEETS 8		





TYPICAL CONSTRUCTION JOINT

SUMMARY OF QUANTITIES

30'5" - 13 @ 36' - 30'5" Continuous Spans; 27'-1" Roadway; Metal Handrail

Bar	A'a	A'a/A'b	A'b	Ba	Ca	B'c	C'c	A'b	B'b	A'f	Ba	Bf	B'f	C'a	Cb	C'b	Db	Ea	E'b	F'a	Ga	S.A	S.B	Ac	Ac/Ad	B'R	B'R	B'c	C'b	B'f	E'b	Bf
No.	82	\	10	28	84	84	112	4	26	1063	252	9	117	18	234	280	20	250	40	260	1302	3448	172	88	16	78		46		\	20	9
Size	#9	#8	#9	#9	#8	#9	#9	#9	#9	#7	#9	#9	#7	#7	#7	#7	#7	#8	#9	#7	#9	#7	#9	#9	#10	#9	#7	#9	#8	#8	8	4
Length	1'8"	\	27'9"	9'8"	27'8"	19'6"	19'6"	27'8"	23'0"	27'8"	1'10"	12'6"	38'0"	42'6"	38'0"	25'6"	42'6"	38'0"	1'8"	21'7"	6'6"	52'6"	6'0"	13'0"	4'0"	13'0"	11'8"	6'0"	24'0"	\	21'7"	21'7"

Concrete Class A(AE)	653.3	Cu. Yd.	Metal Handrail 1,082 Lin. Ft.
Reinforcing Steel	140,452	Lb.	Structural Steel 16,458 Lb.
14"x14" Conc. Piles	3,080	Lin. Ft.	Lin. Ft.
Bearing Devices	7,200	Lb.	Lin. Ft.

REINFORCING DETAIL
BRIDGE NO. 628-23-1669

PREPARED BY
SEDGWICK COUNTY ENGINEERING DEPT.
RUFUS S. KIRK — COUNTY ENGINEER

REVISED	SCALE	DESIGNED	TRACED	CHECKED	SHEET NO.
4-53 W.H.F.	1/4"=1'0"	M.E.S.			7
	DATE				
	PLANFILE		TOTAL SHEETS 8		

Pub. Rd. Div No.	State	Project No.	Fiscal Year	Sheet No.	Total Sheets
5	Kansas		1951		



ELEVATION



END VIEW

V bar

Pile Length	20'6"		24'-6"		28'6"		32'-6"		36'6"		40'6"	
									40 req'd.		40 req'd.	
Bar	Size	Length No.	Size	Length No.	Size	Length No.	Size	Length No.	Size	Length No.	Size	Length No.
V	#7	20'6" 4	#7	24'-2" 4	#7	28'-2" 4	#7	32'-2" 4	#6	36'-2" 4	#6	40'-2" 4
V1									#6	32'-6" 4	#6	36'-0" 4
S	#2	3'-4" 41	#2	3'-4" 49	#2	3'-4" 57	#2	3'-4" 65	#2	3'-4" 73	#2	3'-4" 81
S1	#2	Var 15	#2	Var 15	#2	Var 15	#2	Var 15	#2	Var 15	#2	Var 15
Lift Hook	#8	3'-0" 2	#8	3'-0" 2	#8	3'-0" 2	#8	3'-0" 2	#8	3'-0" 2	#8	3'-0" 2
Jet Pipe												
"a"		6"		6"		6"		6"		6"		6"
"b"		6'-0"		7'-2"		8'-4"		9'-6"		10'-8"		11'-10"
"c"		8'-0"		9'-2"		10'-4"		11'-6"		12'-8"		13'-10"
"d"										1½"		1½"
"e"										28'		32'
x' y' z	⅜ to ⅞ by ⅛		⅜ to ⅞ by ⅛		⅜ to ⅞ by ⅛		⅜ to ⅞ by ⅛		⅜ to ⅞ by ⅛		⅜ to ⅞ by ⅛	
Concrete	.94 Cu. Yds.		1.14 Cu. Yds.		1.34 Cu. Yds.		1.55 Cu. Yds.		1.75 Cu. Yds.		1.95 Cu. Yds.	
Rebar	209 Lbs.		247 Lbs.		284 Lbs.		321 Lbs.		472 Lbs.		524 Lbs.	

Pile Length 37'0"												
Bar	Size	Length No.	Size	Length No.	Size	Length No.	Size	Length No.	Size	Length No.	Size	Length No.
V	#6	36'8" 4										
V1	#6	33'0" 4										
S	#2	3'4" 74										
S1	#2	Var 15										
Lift Hook	#8	3'0" 2										
Jet Pipe		1										
"a"		10"										
"b"		10'-10"										
"c"		11'-11"										
"d"												
"e"												
x' y' z	⅜ to ⅞ by ¼											
Concrete	1.82 Cu. Yds.											
Rebar	482 Lbs.											



"d" Dia. Jet Pipe



#8 Lift Hook



*S1 - 15 bars, increase from "x" to "y" by "z" increments

S & S1 bar

General Notes

Design: According to AASHO Specifications 1949 Edition. Fs=12,000 psi Fc=1,000 psi.
Concrete: Use class A throughout if Piling are to be encased or otherwise protected. Use class A (AE) if piling are to form open bent, unless otherwise noted.
Reinforcing: All dimensions are to center of bars unless otherwise noted.
Jet Pipe: Standard pipe of Dimensions shown unless otherwise approved by Engineer.
Curing: Piling shall be left in forms or otherwise properly cured for at least 7 days. Piling shall not be moved until concrete has attained its design Strength or a minimum of 4 weeks after casting.
Payment: The cost of material and labor used for casting and driving of piles shall be included in the unit bid for concrete piles.
Handling: Piling shall only be lifted by handling hooks or by rigging within 18" of hook location.

14" x 14" Re. Conc. Piling
BRIDGE NO. 628-23-1669

PREPARED BY
SEDGWICK COUNTY ENGINEERING DEPT.
RUFUS S. KIRK — COUNTY ENGINEER

REVISED	SCALE	DESIGNED	TRACED	CHECKED	SHEET NO.
		Schwab	Houseman		8
	DATE	12-51	1-52		
	PLANFILE		TOTAL SHEETS	8	

BY H. Freund DATE 9-8-53 SUBJECT Cantilever Wing SHEET NO. 1 OF 3
CHKD. BY DATE Bri. No. 628-23-1669 JOB NO.



ELEVATION & SECTION (LEVEE SIDE)

Enc. II

BY Freund DATE 10-8-53 SUBJECT Cantilever Wing SHEET NO. 3 OF 3
CHKD. BY DATE Bri. No. 628-23-1669 JOB NO.



SIDE ELEVATION (SHOWING STEEL IN WING ONLY)
Scale $\frac{3}{4}$" = 1'-0"

BY Freund DATE 10-8-53 SUBJECT Cantilever Wing SHEET NO. 2 OF 3
CHKD. BY DATE Bri. No. 628-23-1669 JOB NO.



ELEVATION (WATER SIDE)
Scale 1" = 1'-0"

BY H. Freund DATE 7-1-52 SUBJECT Batter Piling in SHEET NO. 2 OF 2
CHKD. BY DATE Abutments 622-23-1669 JOB NO.
2 Sp. Alt.



BY H. Freund DATE 9-1-53 SUBJECT Batter Piling in SHEET No. 1 OF 2
CHKD. BY DATE Abutments 628-23-1669 JOB NO
2 Sp. Alt.



Enc. III