





SECOND STREET
W.L. DORIS ST. to the W.L. ANNA ST.


TYPICAL SECTIONS OF 30' CONCRETE PAVEMENT
Proj. No. DAKS576041




INTEGRAL CURB



ROLL-TYPE



ALTERNATE ROLL-TYPE



JOINT DETAILS

GENERAL NOTES

- CONTRACTION JOINTS MAY BE CONSTRUCTED IN INTEGRAL CURB BY SAWING WITH AN APPROVED CONCRETE SAW. THE SAW CUT SHALL EXTEND THROUGH THE CURB TO THE PAVEMENT. SAWED CONTRACTION JOINTS SHALL HAVE A MAXIMUM SPACING OF 10'.
- INTEGRAL CURB SHALL BE TIED TO THE PAVEMENT BASE WITH SHORT DEFORMED DOWEL BARS SPACED AT 2'-6" INTERVALS. THESE DOWEL BARS SHALL NOT BE LESS THAN 1/2" OR MORE THAN 3/4" IN DIAMETER.




CITY OF WICHITA, KANSAS
Department of Public Works Engineering Division
R.W. Linn City Engineer
Date: _____ Project No. DAKS576041

B-M

B.M. = 119.03 "G" in Globe, E. Cb. Doris, 2' S. of S.L. 1st St.
 B.M. = 121.44 N.E. Cor. Conc. Porch, House No. 241 N. Doris
 Baseline is Centerline Second St.

NORTH
 SCALE: 1" = 20'



NOTE TO FIELD ENGINEER & CONTRACTOR

- DRAIN TILE HAS BEEN RUD ON THIS PAVING CONTRACT TO INSURE DRAINAGE FOR LOW AREAS BEHIND PROPERTY LINES. THE ENGINEER SHALL DETERMINE IN FIELD THE LOCATIONS REQUIRING THE USE OF DRAINAGE PIPES.
- CONCRETE RETAINING WALL INSTALLATION SHALL BE CONSIDERED AN ALTERNATE BETWEEN STS. 1+50 & 1+60 N.S. 2nd STREET. BOTH THE FIELD ENGINEER AND THE CONTRACTOR SHALL CONTACT PROPERTY OWNER & FURNISH HIM OF THE "GRADING OF PARKING" & "DRIVE WAY CONDITIONS" @ THIS LOCATION. ANY RETAINING WALL CONSTRUCTED SHALL BE ON CITY R/W.
- FENCE AND GUARD POSTS ON S.S. 2ND STREET ACROSS PARK PROPERTY TO REMAIN IN PLACE.
- TAKE TIES AND REPLACE ALL "IRONS" ON THIS PROJECT.

Re-Grade Drainage Ditch (East Side)
 Cost is Incidental to Project.

EARTHWORK:


	CITY	PROPERTY
EXCAVATION	227.2 C.Y.	1010.3 C.Y.
+10%	22.7 C.Y.	101.0 C.Y.
TOTAL	249.9 C.Y.	1111.3 C.Y.
COMP. FILL		36.5 C.Y.
+10%		3.7 C.Y.
TOTAL		40.2 C.Y.

MANIPULATION = 5202.7 S.Y.

SUB-GRADE
 TYPE OF SUB-GRADE TREATMENT SHALL BE DETERMINED BY THE FIELD ENGINEER. SUB-GRADE TREATMENT MAY CONSIST OF LIME TREATMENT, CEMENT TREATMENT, SUB-GRADE MODIFICATION, OR ANY COMBINATION OF THESE.

NOTE TO FIELD ENGINEER & CONTRACTOR
 Grade parking and clear right-of-way for proposed sidewalk. Compact fill in sidewalk area TO BE CONSTRUCTED BY "OTHERS".


NOTE: Trees to be Removed are Marked thus. Except that any Tree Marked for Removal Which in the Opinion of the Engineer Can be Saved, Shall be Spared.




27

SECOND STREET
 W.L. DORIS ST. to W.L. ANNA ST.
 (31' B-B 6" Conc. Pavt. w/ Integral Curb)
CITY OF WICHITA, KANSAS
 R.W. Linn City Engineer
 Proj. No. DAKS576041 Date 7/4

B-M



B-M




NORTH
Scale: 1"=20'

NOTE: Contractor to Contact the Board of Education Regarding the Salvage of Guard Posts Indicated for Removal on Plans.

13+80.00 P
13+79.60 M

GRAVITY TYPE
RETAINING WALL DETAIL



CLASS	H
I	1/2" to 2'-0"
II	2'-0" to 2'-6"
III	2'-6" to 3'-0"

H	W	C.Y. of Conc. per Ft.
1'-6"	10"	0.0370
1'-9"	11"	0.0459
2'-0"	13"	0.0586
2'-3"	15"	0.0729
2'-6"	17"	0.0887
2'-9"	18 1/2"	0.1040
3'-0"	20"	0.1204

NOTE: Bevel all exposed edges 3/4". Taper ends of retaining walls from full height to walk elevation at all locations where retaining walls are constructed adjacent to drives or walks, except where the drives or walks have curbs or retaining walls along the sides. Entire length of tapered section to be included in pay length of retaining wall. Concrete to conform to City of Wichita specifications for Concrete Pavement.