

Sheet 565

ADDENDUM #1

1. Revise the total quantity for the "Surface Coating Finish" for Br. 20.13(W.B.) from 443 square meters to 840 square meters.
2. Revise the total quantity for the "Special Surface Treatment" for Br. 20.13(W.B.) from 152 square meters to 76 square meters (38 sq.m. per abutment).
3. Revise the total quantity for the "Test Pile(Concrete)(325mm)" for Br. 20.13(W.B.) from 37.1 meters to 32.7 meters (Pier No. 1 = 16.6m, Pier No. 2 = 16.1m).
4. Revise the total quantity for the "Surface Coating Finish" for Br. 20.14(E.B.) from 399 square meters to 784 square meters.
5. Revise the total quantity for the "Special Surface Treatment" bid item for Br. 20.14(E.B.) from 152 square meters to 76 square meters (38 sq.m. per abutment).
6. Revise the total quantity for the "Test Pile(Concrete)(325mm)" for Br. 20.14(E.B.) from 37.1 meters to 32.7 meters (Pier No. 1 = 16.6m, Pier No. 2 = 16.1m).
7. Revise the total quantity for the "Pile(Concrete)(325mm)" for Br. 20.14(E.B.) from 1600.0 meters to 1595.5 meters (abutment No. 1 = 251.6m instead of 256.1m).

ADDENDUM #3

The following paragraphs are added to clarify the notes included in the plans regarding painting of the structural steel girders. The referenced plan sheet notes are found under the heading "PAINTING" on Sheet Nos. 435 and 565:

1. Painting of the girders shall generally be in compliance with the KDOT Specifications.
2. The interior portions of the box girders shall receive either two coats in the shop, which consist of an inorganic zinc prime coat (3 mil minimum DFT) and a waterborne acrylic final coat (3 mil minimum DFT); OR, an inorganic zinc prime coat (3 mil minimum DFT) applied in the shop and a waterborne acrylic final coat (3 mil minimum DFT) applied in the field.
3. For either case, the final coat applied to the interior portions of the box girders shall be white.
4. The exterior portions of the box girders shall receive an inorganic zinc prime coat applied in the shop. The exposed exterior portions of the girders shall receive a waterborne acrylic final coat applied in the field after erection. The final coat shall be an approved waterborne acrylic paint in color #20372 (Buckskin) of Federal Standard 59513.