



NOTE: Depth of excavation for subgrade shall be such as to produce a subgrade of uniform thickness which will conform with design for subgrade modification of the road shown below.

The road surface shall be finished to a uniform thickness of 4 inches. The subgrade shall be finished to a uniform thickness of 6 inches. The shoulder shall be finished to a uniform thickness of 6 inches. The road surface shall be finished to a uniform thickness of 4 inches. The subgrade shall be finished to a uniform thickness of 6 inches. The shoulder shall be finished to a uniform thickness of 6 inches.

The road surface shall be finished to a uniform thickness of 4 inches. The subgrade shall be finished to a uniform thickness of 6 inches. The shoulder shall be finished to a uniform thickness of 6 inches. The road surface shall be finished to a uniform thickness of 4 inches. The subgrade shall be finished to a uniform thickness of 6 inches. The shoulder shall be finished to a uniform thickness of 6 inches.

CROWN SECTION
FINISHED ROAD

SUMMARY OF QUANTITIES

DESCRIPTION	QUANTITY	UNIT
Excavation for Subgrade Modification (5.0)	1000.00	Cu Yds.
Excavation for Shoulder Modification	10.00	Cu Yds.
Gravel for Road (6.0) (10.0)	100.00	Cu Yds.
Gravel for Shoulder	10.00	Cu Yds.

Excavation for subgrade modification to be placed on the rate of 1000.00 per cu yd.

QUANTITIES FOR SINGLE RETURN SURFACE TREATMENT

DESCRIPTION	QUANTITY	UNIT
Gravel for Road	100.00	Cu Yds.
Gravel for Shoulder	10.00	Cu Yds.

STANDARD SPECIFICATIONS FOR ROAD CONSTRUCTION
KANSAS DEPARTMENT OF TRANSPORTATION
GRADE MODIFICATION