



Sta 63+61.30 BL A
End Construction 9" Conc Intersection Pavement (6" Crushed Stone Base). Begin Construction 9" NRDJ Concrete Pavement on 6" Crushed Stone Subgrade on Geogrid Reinforcement

Sta 64+06.90 BL A
Construct 31.0' Commercial Drive Ent (8" Reinf Concrete) to PL. Saw & Remove Exstg Asph Parking Pvmnt as shown and Replace w/ 6" Asph Parking Pvmnt. Match Exstg @ Saw Cut.

Sta 64+38.83 BL A
Construct 24.0' Commercial Drive Ent (8" Reinf Concrete) to PL. Saw & Remove Exstg Asph Parking Pvmnt as shown and Replace w/ 6" Asph Parking Pvmnt. Match Exstg @ Saw Cut.

Sta 65+01.17 BL A
Construct 35.0' Commercial Drive Ent (8" Reinf Concrete) to PL. Saw & Remove Exstg Asph Parking Pvmnt as shown and Replace w/ 6" Asph Parking Pvmnt. Match Exstg @ Saw Cut.

Sta 65+49.85 BL A
Construct 30.0' Commercial Drive Ent (8" Reinf Concrete). Match @ PL.

Construct 9" NRDJ Concrete Pavement on 6" Crushed Stone Subgrade on Geogrid Reinforcement

Construct 5.0' Conc Walk. (6" Reinf)

End Construct 5.0' Conc Walk. (6" Reinf) @ Nearest Joint. Match Exstg Walk Grade.

715

Sta. 66+58.70, 50.0' Lt., R/W PI

Construct 9" NRDJ Concrete Pavement on 6" Crushed Stone Subgrade on Geogrid Reinforcement

Construct Std Comb Curb & Gutter (Type I)(AE)

Construct 5.0' Conc Walk. (4"thk)

Construct Std Comb Low Edge Median Curb & Gutter (8"x 1.75")(Type III)(AE) and 6.0' Solid Conc Median Ramp-type Nose Section (Typical Each End). Construct Deco Brick Median Pavement. See Central Paving Plan Sheet

Remove & Relocate Ex. Parking Stops.

Construct 5.0' Conc Walk. (6" Reinf)

Construct Std Comb Curb & Gutter (Type I)(AE)

Construct 5.0' Conc Walk. (6" Reinf)

Sta. 64+61.25, 60.0' Lt., R/W PI
Sta. 64+61.25, 703
50.0' Lt., R/W PI

Sta. 66+58.70, 50.0' Lt., R/W PI

Adj MH Top El.=122.64

Adj MH Top El.=122.55

Adj MH Top El.=122.09

El. = 122.56

El. = 122.50

Sta. 63+51.80, 60.0' Rt., R/W PI

Sta. 63+34.94, 75.0' Rt., R/W PI

Construct Conc. Bus Stop Landing. Per City Specs. Remove, Protect, & Reset Ex. Bench

Construct 5.0' Conc Walk. (4"thk)

Saw & Match Exstg Walk Grade.

Sta 61+79.73 BL A
End Construction 9" NRDJ Concrete Pavement on 6" Crushed Stone Subgrade on Geogrid Reinforcement. Begin Construction 9" Concrete Intersection Pavement (6" Crushed Stone Base).

Construct 5.0' Conc Walk. (6" Reinf)

Construct Std Comb Curb & Gutter (Type I)(AE)

Decorative Brick Pavers Crosswalk Pavement Typical all approaches - See Dtl Sheet

P.V.I. No V.C. Elev=121.69Tc

Note:
Trees/Shrubs to be removed are marked thus:

Note:
Pavement, Sidewalks, and Etc. To Be Removed Are Indicated By:

Drawing File: E:\Eng\West Street Paving New\Land\dwg\Bases
Design: T. Azire
Drawn: Sonny
Approved: J. F. Bradley
Scale: 1:20
Project No. 0404.E859 CAPITAL IMPROVEMENT PROJECT
WEST STREET PAVING
Sta 61+50.00 BL A to Sta 65+83.55 BL A
PAVEMENT, STORM WATER SEWER, TRAFFIC CONTROL IMPROVEMENTS

Baughman Company, P.A.
315 Ellis St. Wichita, KS 67211 P 316-262-7271 F 316-262-0149
ENGINEERING | SURVEYING | PLANNING | LANDSCAPE ARCHITECTURE

November 2008
SHEET 18 OF 131