


NORTH



HORIZ. (FEET)
0 20 40
GRAPHIC SCALE FOR 1" = 20'

LEGEND:

- TC = Top of Curb Elev.
- FL = Pavement Flowline Elev.
- GND = Ground Elev.
- 1375 = Proposed Contours, 1-ft. intervals
- ↖ = Direction of surface water runoff.

EARTHWORK NOTES:

1. THE CONTRACTOR SHALL STRIP ALL VEGETATION, ORGANIC TOPSOIL, TREES (AND MAJOR ROOTS), EXISTING STRUCTURES, FOUNDATIONS, SLABS, AND PAVEMENTS FROM ALL PROPOSED PAVED AREAS. TREES, BUSHES, AND STUMPS SHALL BE REMOVED AND/OR GROUND DOWN TO 18-INCHES BELOW EXISTING GRADE.
2. PRIOR TO PLACING FILL IN PROPOSED PAVMENT AND WALK AREAS, ALL AREAS TO RECEIVE FILL SHALL BE PROOF ROLLED PER SPECIFICATIONS. ALL SOFT AREAS SHALL BE UNDERCUT TO FIRM SOILS AND BACKFILLED WITH COMPACTED FILL AS INDICATED BELOW.
3. SUITABLE SOIL MATERIALS FOR FILL SHALL BE FREE FROM ORGANIC CONTAMINANTS, WEIGH MORE THAN 90 LBS./CU.FT.(LABORATORY DRY WEIGHT DENSITY), FREE OF ANY OBJECTIONABLE MATERIALS, AND CAPABLE OF BEING COMPACTED TO 95% OF MAX. DRY DENSITY AS DETERMINED BY ASTM D698.
4. REFER TO THE GEOTECHNICAL REPORT FOR SUB-GRADE PREPARATION AND SITE GRADING REQUIREMENTS.



WDM Architects P.A.
105 North Washington
Wichita, KS 67202-2
T 316.262.4700
F 316.262.0002
wdmarchitects.com

we do more

Neurology Consultants of Kansas
Wichita, Kansas

PRINTS ISSUED
06/08/09 Concept Review
06/23/09 Preliminary Review
07/13/09 GMP Pricing
08/14/09 Permit submittal
10/12/09 For Construction

WDM No. 08135
drawn: ELS
checked: CRY

SITE GRADING & DRAINAGE P

C2

YOUNG & ASSOCIATES, P.A.
Professional Civil Engineering Consultants
100 South George, Derby, Kansas 67037
tele: (316)788-2552, fax: (316)788-4408, email: young@enamain.com

