

# GENERAL NOTES

- Utility service lines, poles, valve boxes, gas meters, and etcetera are to be adjusted as necessary by others prior to construction unless the plans specifically call for their adjustment by the Contractor or unless the plans specifically identify a utility to be adjusted by its owner during construction. Existing utilities and their location, as shown on the plans, represent the best information obtainable for design. The Contractor will be required to work around existing utilities within the right-of-way which do not conflict with proposed construction.
- The Contractor shall give all property owners and/or tenants of developed property abutting the project limits a minimum of ten (10) days advance notice prior to start of construction.
- Contractor will be required to provide a minimum advance notice of forty-eight (48) hours to utility companies prior to excavation or working adjacent to utilities. Kansas One-Call 687-2470
- A full depth saw cut of the existing pavement shall be provided at locations where proposed construction abuts an existing surface course or pavement for which partial removal of that surface or pavement is required. Sawed joint to facilitate removal within three (3) feet of existing joints will not be permitted and for such instances the limits or removal shall extend to the existing joint. Such saw cuts will not be paid for directly and this cost shall be considered SUBSIDIARY to the removal of the surface or pavement.
- All project waste including any trees, milled asphalt, rubble from miscellaneous structures, abandoned pipes, excess excavation & etc. shall be disposed of on sites to be provided by the Contractor. These sites shall be approved by the Engineer as to suitability, appearance and site location. Locations that, in the opinion of the Engineer, will leave an unsightly appearance will not be approved. All disposal sites must be approved by the Kansas Department of Health and Environment. Material either stockpiled or disposed of in a flood plain would require a Kansas State Board of Agriculture permit. Any material dumped in waters of the United States or wetlands is subject to U.S. Corps. of Engineers permitting regulations. Any material buried or stockpiled beyond approved construction limits would require additional archaeological investigations unless buried in a previously approved borrow location.
- The Construction Engineer shall be responsible for preserving all sections line monuments. The Construction Engineer shall take accurate ties to said monuments as well as submittal of the required forms to the Dept. of Archives, Kansas State Historical Society. Survey monuments will be furnished by the City.
- Prior to bidding the project, each bidder shall visit the site and satisfy himself of surface & subsurface conditions. Each bidder shall also fully inform himself as to the extent of the scope of work to be performed.
- Contractor shall be aware that some gas & telephone lines within the project corridor may have been abandoned in place as new lines are installed. The Contractor shall be responsible for contacting the appropriate owners to determine the status of said lines.
- The Water Department shall field locate water valves one time during construction when requested by the Contractor. It shall be the Contractor's responsibility to preserve such field locations during the construction process. Water valves, water valve boxes or fire hydrant damaged during construction shall be repaired by the Contractor at his own expense.
- The Contractor shall be made aware that he will be working in close proximity of existing utilities. Any conflicts with such utilities shall be reported to the Engineer. The Contractor shall coordinate the construction of this project with relocation of any existing utilities by the utility companies.
- Properties within the project limits may have underground sprinkler systems in public right-of-way which conflict with new construction. The Contractor will be required to repair or replace any system disturbed by project construction. Portions of underground sprinkler systems not in conflict with new construction shall be protected from damage and shall remain in place. The portions of the sprinkler system that are to remain in place shall be returned to working order so that landscaped areas outside of the construction area can be irrigated during construction. All work in connection with underground sprinkler systems shall be SUBSIDIARY to the bid item "Private Sprinkler System Restoration" (Non-Participating).
- The Contractor shall remove and deliver to the Central Maintenance Facility, 1801 S. McLean, all regulatory signs, street name signs, information signs, and etc. that conflict with the proposed construction. Cost of removal and delivery shall be SUBSIDIARY to the bid item "Transportation of Salvage Material" (Non-Participating)
- Trees and Shrubs in public right-of-way which are in direct conflict with proposed new construction shall be removed and disposed of by the Contractor with the Engineer's approval. Trees and shrubs which are not in direct conflict with proposed new construction shall be saved and protected from damage.
- All areas disturbed by the construction that are adjacent to developed properties shall be restored with the same as to match existing turf type. Restoration of disturbed areas shall include, but not be limited to, top soil preparation and sodding. All sodding work shall be in accordance with City Standard specifications and the City Administrative Regulations No. AR78, which governs cleanup and restoration or replacement following construction. The "Recapitulation of Quantities" shows the estimated Square Yards of sodding, with a bid item for the same. When the weather/season prevents the installation of sod, the Contractor shall be responsible for installing Erosion Control Blanket (Curlex 1, or approved equal) at the back of curb (8' wide minimum). All costs for erosion control mat installation shall be SUBSIDIARY to "Site Restoration".
- All areas disturbed by construction that are adjacent to non-developed properties shall be restored by seeding with a mixture of Ryegrass (applied at a rate of 200lbs. per acre) and Fescue, Bermuda, or Buffalo grass, depending on the soil conditions (applied per Standard Specifications). Pure Nitrogen fertilizer shall also be applied at a rate of 1.5 lbs. per thousand square feet. The seed shall be watered with deep soaking every two (2) weeks during dry periods until a mature stand of grass is obtained. The "Recapitulation of Quantities" shows the estimated Square Yards of seeding, with a bid item for the same. The permanent seeding may be omitted only if sodding is required in accordance with previous General Note. The Contractor shall be responsible for installing Erosion Control Blanket (Curlex 1, or approved equal), at the back of curb, to and including the limits of the seeded areas. All costs for this work shall be SUBSIDIARY to the seeding bid item.
- Contractor shall be responsible for implementing erosion control methods during construction to prevent unnecessary silt/sediment discharge through downstream properties and/or storm sewer systems. Contractor shall install and maintain erosion controls as directed by the Engineer. These controls may include, but not limited to: hay bales; silt fences, temporary mulching or other controls necessary to inhibit sediment runoff during construction.
- All sign post, light pole and traffic signal removal shall include removal of footings as SUBSIDIARY to such removal.
- The Contractor shall not start work on the Project until the Project Inspector is assigned and is present on site. Any work done without inspection will be required to be uncovered for inspection.
- New Sidewalk shall have a maximum side slope of not more than one-quarter inch (1/4") per foot and a maximum longitudinal slope of two (2) percent unless otherwise approved by the Engineer. The sidewalk location shown on the plan is tentative. The Contractor shall be aware that the final sidewalk alignment may be subject to field changes based on the new location of power poles, utility pedestals, and trees. However, the Contractor shall make every effort to adhere to the sidewalk plan with respect to slope and drainage conditions. Baughman Co. will provide staking coordinates for the shown sidewalk alignment during construction.
- Fences within the public right-of-way which are in direct conflict with proposed new construction shall be removed by and become property of the Contractor with the Engineer's approval. Cost to be SUBSIDIARY to "R/W Clearing and Site Preparation".
- Areas over-excavated in surface or pavement removal shall be filled to sub grade elevation and compacted to 95% Std. Density. Cost shall be SUBSIDIARY to the Project.
- Geogrid Reinforcement for the rock base shall be Tensor BX1100 as manufactured by the Tensor Corporation, or Geolon HP570 as manufactured by Mirafi Corporation. Geogrid fabric shall be SUBSIDIARY to the installation of the Reinf. Crushed Rock Base.
- When Beginning or Ending Full Height Curb, the Height of the Curb shall Transition between 1.5" to 6" in a minimum of 5.00'.
- The crushed rock base under valley gutters, concrete pavement, and bituminous pavement shall conform to the following limits:

Sieve Size	% Passing
2-1/2"	100
3/4"	40-80
No. 4	20-50
No. 40	6-20
No. 200	2-10

Rock quality shall conform to the requirements specified by the KDOT 1990 Edition Standard Specification, Subsection 1102 for Durability Class 1.
- The Contractor shall comply with all applicable safety regulations.
- The existing sanitary sewer manholes that are to be adjusted to match final grade are plastic lined. Any adjustment rings, cone sections, offset cone sections, etc. necessary for the adjustment shall either be lined or coated with an approved coating. Any damage to the existing plastic lining during the manhole adjustment shall be repaired. Cost for this work shall be considered SUBSIDIARY to the manhole adjustment.
- Existing and Proposed Power Poles may require bracing during certain phases of the Project. The Contractor shall be responsible for coordinating the pole bracing with Raymond Lara with Westar Energy at 261-6630.
- Valve Boxes and Water Meters within the Project Limits shall be adjusted to match Final Grade. Cost to be SUBSIDIARY to the bid item "Adjustment of Water Valves" (Non-Participating).
- The Contractor shall salvage the Bridge Rails and Brackets from the existing wooden timber bridge that is to be removed. These parts shall be deliver to the City of Wichita West Substation at 661 N. Elder. Cost of removal and delivery shall be SUBSIDIARY to the bid item "Transportation of Salvage Material" (Non-Participating)
- The Contractor shall install a 2" RGC Interconnect along 37th Street North from Tyler to Ridge. See the Marking & Signing Plans for more information. Cost of the material and installation to be SUBSIDIARY to the Lump Sum Bid Item "Traffic Signal Interconnect".
- The Contractor shall notify the Maize School District USD 266 prior to beginning construction so that school bus routes can be adjusted as necessary. USD 266 Transportation Department: 722-0582
- TRAFFIC CONTROL:  
One lane of traffic in each direction must be maintained on 37th Street North west of the bridge & Tyler Road during construction. Contractor shall provide, erect, and maintain traffic control devices in accordance with the Manual on Uniform Traffic Control Devices (M.U.T.C.D.) as shown on the Traffic Control plans and subject to the Engineer's approval. Access to Residences & Businesses shall be maintained at all times.

## LIST OF UTILITY COMPANIES

Contractor shall be required to provide notice to Kansas One Call at 687-2470 a minimum of two (2) working days prior to any excavation or work adjacent to utilities.

TYPE	OWNER	CONTACT	TELEPHONE	(ALT.)
Locator Service	Kansas One-Call		687-2470	800-344-7233
TV	Cox Communications	Marc Henderson	262-4270	
Electric	Westar Energy	Miles Capps	261-6512	
Gas	Aquila Energy	Calvin Briggs	941-1608	
Telephone	AT&T Telephone	Jim Tobin	268-2759	800-286-8313
Water	Wichita Water Department	Bill Perkins	268-4563	268-4908
Storm Water Sewer	Wichita SWS Maintenance	Doug Arvidson	268-4095	
Sanitary Sewer	Wichita Sewer Maintenance	Calvin Fugit	268-4024	262-6000
Ground Water	Ground Water Management #2		(316) 835-2224	
Railroad	K & O Railroad	Neil Jacobs	(316) 261-6172	(316) 261-6172