

STATE	PROJECT NO.	YEAR	SHEET NO.	TOTAL SHEETS
KANSAS	472 84614	:	74	534

SEC/COR NO.	QUARTER CORNER LOCATION	COORDINATES		CORNER DESCRIPTION	STATION	OFFSET (FT)	ANGLE	TIE	DISTANCE (FT)	DIRECTION	TIE DESCRIPTION
		NORTHING	EASTING								
205	S 1/4 Cor. Sec. 22, T27S, R2E	1683881.7292	1689113.0847	*4 Rebar with Baughman Cap in Thimble	600+71.73 Zella St. 49+70.50	29.50 Lt. 0.00 Lt.	90°01'47" NW	R1	84.05	SW	Chiseled cross cut on traffic signal base
								R2	94.74	SE	Chiseled cross cut on traffic signal base
								R3	64.10	NE	Chiseled cross cut on traffic signal base
								R4	66.00	NW	Chiseled cross cut on traffic signal base
206	SW Cor. Sec. 23, T27S, R2E	1683925.0841	1691762.3417	*5 MKEC	627+21.90 127th St. 50+02.14	2.14 Rt. 0.00 Lt.	90°24'00" SE	R1	1.50	S	North edge of eastbound shoulder
								R2	83.00	SW	Nail in cap in light pole
								R3	88.20	SW	Centerline of SBC manhole
								R4	115.20	SE	Gas pipeline marker
								R5	144.30	NW	Fence corner post, fence east, northeast, southwest
								R6	178.80	NE	3 nails in highline pole
207	S 1/4 Cor. Sec. 23, T27S, R2E	1683983.9978	1694410.8031	*5 Rebar in Thimble	653+71.02	2.14 Rt.	90°23'10" SE	R1	--	N & S	Tree line
								R2	110.10	N	Nail in washer top of brace post
								R3	111.64	NNE	Nail in washer top of brace post
								R4	119.06	S	Nail in washer top of brace post
								R5	57.11	W	Chiseled cross cut on drop inlet
208	SW Cor. Sec. 24, T27S, R2E	1684042.6246	1697049.5335	*4 Baughman Rebar (Set)	680+11.13 143rd St. 50+32.00	32.00 Rt. 0.00 Lt.	90°04'25" SE	R1	98.85	SW	Chiseled cross on signal pole base
								R2	93.44	SE	Chiseled cross on signal pole base
								R3	84.42	NE	Chiseled cross on signal pole base
								R4	79.12	NW	Chiseled cross on signal pole base
209	S 1/4 Cor. Sec. 24, T27S, R2E	1684086.1048	1699684.0765	*4 Baughman Rebar (Set)	706+46.67 (Bk. Tan.)	1.92 Lt.	87°04'36" NW (Bk. Tan.)	R1	97.99	SSW	Chiseled cross cut on fence corner base
								R2	55.75	W	Chiseled cross cut on drop inlet
								R3	71.30	NNE	Top of right-of-way monument
								R4	93.69	NW	Chiseled cut on high line pole base
210	SW Cor. Sec. 19, T27S, R3E	1684130.0028	1702321.6939	*5 Rebar in Thimble	732+84.76 159th St. 49+89.78	10.22 Lt. 0.00 Lt.	89°55'49" NW	R1	97.60	SE	Nail and washer in light pole
								R2	98.00	SW	Nail and washer in light pole
								R3	99.50	SW	Top of right-of-way monument
								R4	85.00	NE	USGS Monument
211	W 1/4 Cor. Sec. 19, T27S, R3E	1686783.4130	1702283.1162	Concrete Monument	159th St. 23+36.09	0.00 Lt.		R1	30.40	ENE	Nail in cap in power pole
								R2	35.20	NW	PK nail in hedge tree
								R3	47.50	SW	PK nail in hedge tree
								R4	30.00	W	*5 rebar with yellow cap
212	Center of Sec. 24, T27S, R2E	1686738.6964	1699645.3190	*4 Rebar with Baughman Company Cap				R1	0.50	WSW	Steel fence corner post
								R2	--	N, S, E, & W	Line of tree lines
								R3	12.15	S	40d nail in 1 1/2" Hackberry
								R4	1.90	N	Wrought iron fence corner
								R5	14.20	E	PK nail in cap in hedge tree
213	W 1/4 Cor. Sec. 24, T27S, R2E	1686698.8786	1697009.1081	*5 Rebar	680+11.13 143rd St. 23+75.44	2624.56 Lt. 0.00 Lt.	90°04'25" NW	R1	51.15	W	3 nails in brace post
								R2	--	E & W	Tree line
								R3	--	N & S	Centerline of road
								R4	52.00	ESE	Mag in power pole
								R5	56.70	SE	Chain link fence corner
								R6	51.90	WSW	Gas test
214	Center of Sec. 23, T27S, R2E	1686640.4253	1694369.6915	Metal Cap LS - 1126	653+71.02	2654.61 Lt.	90°23'10" NW	R1	21.60	S	Chiseled cross cut on retaining wall
								R2	47.00	E	Chiseled cross cut on RCP
								R3	10.50	NW	Shoulder NE bound Turnpike
								R4	67.10	NNW	Chiseled cross cut top of centerline of wall
215	W 1/4 Cor. Sec. 23, T27S, R2E	1686582.4754	1691721.7917	1" Iron Pipe in Thimble	627+21.90 127th St. 23+42.30	2655.56 Lt. 0.00 Lt.	90°24'01" NW	R1	60.80	SE	3 nails in top of fence post
								R2	59.10	NW	Top of steel fence corner post
								R3	46.10	SW	Top of fire hydrant
								R4	46.40	NW	3 nails in light pole
216	Center of Sec. 22, T27S, R2E	1686542.0000	1689073.9768	100D Spike	Zella St. 23+09.94	0.00 Lt.		R1	--	E & W	Centerline of road
								R2	34.80	S	Bent 60d nail in hedge tree
								R3	29.30	N	3 nails in power pole
								R4	71.35	NW	PK nail in guy pole
								R5	36.00	SW	PK nail in light pole
225	Center of Sec. 27, T27S, R2E	1681227.8883	1689148.3159	*5 Rebar With MKEC Cap	600+71.73 Zella St. 76+24.57	2,624.57 Rt. 0.00 Lt.	90°01'47" SE	R1	4.00	N	Chiseled cross cut on curb
								R2	13.90	S	Chiseled cross cut on curb
								R3	20.00	SW	Chiseled cross cut on curb
								R4	18.30	SE	Chiseled cross cut on curb
								R5	33.40	NE	Square cut east end headwall RCBC
226	W 1/4 Cor. Sec. 26, T27S, R2E	1681274.1284	1691796.5656	*4 Rebar	127th St. 76+53.32	0.00 Lt.		R1	26.35	E	Steel fence corner post
								R2	--	E	Line of tree line
								R3	34.30	NW	Chiseled cross on southeast gas meter guard post
								R4	37.65	SE	PK nail in power pole
								R5	70.30	SW	PK nail in power pole
228	W 1/4 Cor. Sec. 25, T27S, R2E	1681387.8614	1697079.7227	*4 Rebar	143rd St. 76+86.93	0.00 Lt.		R1	38.40	W	PK nail in power pole
								R2	33.10	ESE	Chiseled cross cut on RCP
								R3	53.90	NE	PK nail in power pole
								R4	68.50	WNW	South end wrought iron fence
229	Center of Sec. 25, T27S, R2E	1681434.7013	1699727.6085	3/4" Iron Pipe with LS555 Cap	706+46.67 (Bk. Tan.)	2649.84 Rt.	87°04'36" SE (Bk. Tan.)	R1	2.73	NW	Mag nail in fence corner
								R2	80.97	NE	Southeast corner of metal building
								R3	127.23	SE	Southeast corner of garage house * 15210
								R4	189.59	W	Chiseled cross cut on curb

CITY OF WICHITA

SECTION CORNERS

10:41:59 AM  
 2/9/2011  
 T:\35766A\Cadd\Sheets\General\K25ECCOR01.dgn  
 SURV. - PLOT CADD DES. - DR. - TR. - CKD. - APP.