



BEAM REPAIR PLAN

- Note:**
1. For Concrete Repair Procedures See Sheet No. 30.
 2. Fillets to be repaired considered "Concrete Beam Repair" measured horizontally to face of pier.

BRIDGE RAIL REPAIR

Type	No. Locations
A	19
B	2

Note: See Sheet 30 for repair details.

- Legend**
- Spalled and Deteriorated Sidewalk Floor Beam and Slab Areas to be Repaired.
 - A Type A Rail Repair (See Sht. No. 31)
 - B Type B Rail Repair (See Sht. No. 31)
 - Fillet Fillets to be repaired

No.	Revisions	By	Date

CITY OF WICHITA, KANSAS
 JAMES L. ARMOUR, P.E. - ACTING CITY ENGINEER
 MURDOCK BRIDGE
 OVER LITTLE ARKANSAS RIVER
CONCRETE BEAM AND SLAB REPAIR
 CITY OF WICHITA PROJECT NO. 472-83895

Professional Engineering Consultants, P.A.
 303 S. TOPEKA • WICHITA, KANSAS 67202
 316-262-2691 • FAX 316-262-3003

Designed by	R.A.S.	Checked by	R.A.S.
Drawn by	R.A.S./W.L.L.	Date	July 2003
		Job No.	96940-2

usr/ustm/dgn/1996/96940/002/officecheck/beamf1.r.dgn
 drawn by : ras/wll
 plotted by : RAS 3-27-2004