

* Offset dimension for inlets are measured from the inside face of the box structure nearest the curb to the centerline of the street right of way

BL Sta 26+87.40 37.69' Lt. Light Fixture
BL Sta 26+92.94 Lt. 1-6" RCMH Top=111.57 FL(NE)=105.36 FL(W)=105.56 FL(SE)=106.96

Sta 27+70.99 Douglas= Sta 85+00.00 Sycamore

Sta 27+63.94 3.74' Lt. Radius Point

Remove Existing Inlet Plug Pipe (N)

Remove 65 LF 24" RCP

40' R/W

Relocate Pole (by others)

80 S.F. 5'x4" Sidewalk

Remove Existing Inlets

Remove Existing Traffic Signal

Remove Existing Inlet

Construction Limits

MATCH LINE STA 86+00

KGE MH. See note 1 Sheet CV 1.1

Remove Existing Traffic Signal

Remove Existing Traffic Signal

40' R/W

BL Sta 28+28.90 36.55' Lt. Light Fixture

KGE MH. See note 1 Sheet CV 1.1

50' R/W

BL Sta 29+10.29 38.80' Lt. Light Fixture

KGE MH. See note 1 Sheet CV 1.1

BL Sta 28+92.00 40.94' Rt. Exist Westar MH No Adjustment Required Replace KGE MH Lid w/ City of Wichita MH Lid

Planter Drains See Arch. Plans

BL Sta 29+97.79 38.80' Lt. Light Fixture

BL Sta 28+85.75 7.50' Rt. Crown

Remove all mast arm poles, cabinet controllers junction boxes, lids, etc. and return to 1801 S. McLean. Contact signal supervisor at 268-4033 24 hrs prior to construction. Existing Westar Conduit and manholes to be abandoned by Westar Energy. City of Wichita to assume ownership of south side conduit. Light Pole bases to be removed by Westar.

Remove Existing Inlet

Remove Existing Traffic Signal

Remove Existing Inlet

Remove 44 LF 21" RCP

Remove 18 LF 15" RCP

Remove 94 LF 15" RCP

Existing SW to Remain

BL Sta 83+80.04 14.45' Rt.* Install 1-Type 1A Curb Inlet MH Top=110.95 FL(NW)=107.69 FL(W)=107.79

BL Sta 83+48.55 Begin Removal and Reconstruction Sawcut & Match Exist. Pavement

BL Sta 27+68.89 41.81' Rt. Adjust MH Top=110.97 Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 28+10.29 37.00' Rt. Light Fixture

BL Sta 28+80.45 41.10' Rt. Adjust MH Top=111.36 Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 28+94.43 37.50' Rt. Light Fixture

BL Sta 29+84.89 38.10' Rt. Light Fixture

Construct 29' Concrete Drive Approach (Sheet CV 4.9) 230 S.F. 8" Reinf. Conc.

BL Sta 29+44.89 38.10' Rt. Light Fixture

BL Sta 29+76.10 38.10' Rt. Light Fixture

BL Sta 26+23.60 Type 2 Curb Inlet MH Top=111.59 FL(N)=108.33 FL 4" Stub (N)=108.59

BL Sta 27+05.77 40.19' Rt. Existing KGE MH No Adjustment Required Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 26+56.15 38.10' Rt. Light Fixture

BL Sta 25+73.86 41.19' Rt. Adjust MH Top=111.87 Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 25+76.10 38.10' Rt. Light Fixture

BL Sta 26+87.40 37.69' Lt. Light Fixture

BL Sta 26+92.94 Lt. 1-6" RCMH Top=111.57 FL(NE)=105.36 FL(W)=105.56 FL(SE)=106.96

BL Sta 27+70.99 Douglas= Sta 85+00.00 Sycamore

BL Sta 27+63.94 3.74' Lt. Radius Point

Remove Existing Inlet Plug Pipe (N)

Remove 65 LF 24" RCP

40' R/W

Relocate Pole (by others)

80 S.F. 5'x4" Sidewalk

Remove Existing Inlets

Remove Existing Traffic Signal

Remove Existing Inlet

Construction Limits

MATCH LINE STA 86+00

KGE MH. See note 1 Sheet CV 1.1

Remove Existing Inlet

Remove Existing Traffic Signal

Remove Existing Inlet

Remove 44 LF 21" RCP

Remove 18 LF 15" RCP

Remove 94 LF 15" RCP

Existing SW to Remain

BL Sta 83+80.04 14.45' Rt.* Install 1-Type 1A Curb Inlet MH Top=110.95 FL(NW)=107.69 FL(W)=107.79

BL Sta 83+48.55 Begin Removal and Reconstruction Sawcut & Match Exist. Pavement

BL Sta 27+68.89 41.81' Rt. Adjust MH Top=110.97 Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 28+10.29 37.00' Rt. Light Fixture

BL Sta 28+80.45 41.10' Rt. Adjust MH Top=111.36 Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 28+94.43 37.50' Rt. Light Fixture

BL Sta 29+84.89 38.10' Rt. Light Fixture

Construct 29' Concrete Drive Approach (Sheet CV 4.9) 230 S.F. 8" Reinf. Conc.

BL Sta 29+44.89 38.10' Rt. Light Fixture

BL Sta 29+76.10 38.10' Rt. Light Fixture

BL Sta 26+23.60 Type 2 Curb Inlet MH Top=111.59 FL(N)=108.33 FL 4" Stub (N)=108.59

BL Sta 27+05.77 40.19' Rt. Existing KGE MH No Adjustment Required Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 26+56.15 38.10' Rt. Light Fixture

BL Sta 25+73.86 41.19' Rt. Adjust MH Top=111.87 Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 25+76.10 38.10' Rt. Light Fixture

BL Sta 26+87.40 37.69' Lt. Light Fixture

BL Sta 26+92.94 Lt. 1-6" RCMH Top=111.57 FL(NE)=105.36 FL(W)=105.56 FL(SE)=106.96

BL Sta 27+70.99 Douglas= Sta 85+00.00 Sycamore

BL Sta 27+63.94 3.74' Lt. Radius Point

Remove Existing Inlet Plug Pipe (N)

Remove 65 LF 24" RCP

40' R/W

Relocate Pole (by others)

80 S.F. 5'x4" Sidewalk

Remove Existing Inlets

Remove Existing Traffic Signal

Remove Existing Inlet

Construction Limits

MATCH LINE STA 86+00

KGE MH. See note 1 Sheet CV 1.1

Remove Existing Inlet

Remove Existing Traffic Signal

Remove Existing Inlet

Remove 44 LF 21" RCP

Remove 18 LF 15" RCP

Remove 94 LF 15" RCP

Existing SW to Remain

BL Sta 83+80.04 14.45' Rt.* Install 1-Type 1A Curb Inlet MH Top=110.95 FL(NW)=107.69 FL(W)=107.79

BL Sta 83+48.55 Begin Removal and Reconstruction Sawcut & Match Exist. Pavement

BL Sta 27+68.89 41.81' Rt. Adjust MH Top=110.97 Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 28+10.29 37.00' Rt. Light Fixture

BL Sta 28+80.45 41.10' Rt. Adjust MH Top=111.36 Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 28+94.43 37.50' Rt. Light Fixture

BL Sta 29+84.89 38.10' Rt. Light Fixture

Construct 29' Concrete Drive Approach (Sheet CV 4.9) 230 S.F. 8" Reinf. Conc.

BL Sta 29+44.89 38.10' Rt. Light Fixture

BL Sta 29+76.10 38.10' Rt. Light Fixture

BL Sta 26+23.60 Type 2 Curb Inlet MH Top=111.59 FL(N)=108.33 FL 4" Stub (N)=108.59

BL Sta 27+05.77 40.19' Rt. Existing KGE MH No Adjustment Required Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 26+56.15 38.10' Rt. Light Fixture

BL Sta 25+73.86 41.19' Rt. Adjust MH Top=111.87 Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 25+76.10 38.10' Rt. Light Fixture

BL Sta 26+87.40 37.69' Lt. Light Fixture

BL Sta 26+92.94 Lt. 1-6" RCMH Top=111.57 FL(NE)=105.36 FL(W)=105.56 FL(SE)=106.96

BL Sta 27+70.99 Douglas= Sta 85+00.00 Sycamore

BL Sta 27+63.94 3.74' Lt. Radius Point

Remove Existing Inlet Plug Pipe (N)

Remove 65 LF 24" RCP

40' R/W

Relocate Pole (by others)

80 S.F. 5'x4" Sidewalk

Remove Existing Inlets

Remove Existing Traffic Signal

Remove Existing Inlet

Construction Limits

MATCH LINE STA 86+00

KGE MH. See note 1 Sheet CV 1.1

Remove Existing Inlet

Remove Existing Traffic Signal

Remove Existing Inlet

Remove 44 LF 21" RCP

Remove 18 LF 15" RCP

Remove 94 LF 15" RCP

Existing SW to Remain

BL Sta 83+80.04 14.45' Rt.* Install 1-Type 1A Curb Inlet MH Top=110.95 FL(NW)=107.69 FL(W)=107.79

BL Sta 83+48.55 Begin Removal and Reconstruction Sawcut & Match Exist. Pavement

BL Sta 27+68.89 41.81' Rt. Adjust MH Top=110.97 Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 28+10.29 37.00' Rt. Light Fixture

BL Sta 28+80.45 41.10' Rt. Adjust MH Top=111.36 Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 28+94.43 37.50' Rt. Light Fixture

BL Sta 29+84.89 38.10' Rt. Light Fixture

Construct 29' Concrete Drive Approach (Sheet CV 4.9) 230 S.F. 8" Reinf. Conc.

BL Sta 29+44.89 38.10' Rt. Light Fixture

BL Sta 29+76.10 38.10' Rt. Light Fixture

BL Sta 26+23.60 Type 2 Curb Inlet MH Top=111.59 FL(N)=108.33 FL 4" Stub (N)=108.59

BL Sta 27+05.77 40.19' Rt. Existing KGE MH No Adjustment Required Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 26+56.15 38.10' Rt. Light Fixture

BL Sta 25+73.86 41.19' Rt. Adjust MH Top=111.87 Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 25+76.10 38.10' Rt. Light Fixture

BL Sta 26+87.40 37.69' Lt. Light Fixture

BL Sta 26+92.94 Lt. 1-6" RCMH Top=111.57 FL(NE)=105.36 FL(W)=105.56 FL(SE)=106.96

BL Sta 27+70.99 Douglas= Sta 85+00.00 Sycamore

BL Sta 27+63.94 3.74' Lt. Radius Point

Remove Existing Inlet Plug Pipe (N)

Remove 65 LF 24" RCP

40' R/W

Relocate Pole (by others)

80 S.F. 5'x4" Sidewalk

Remove Existing Inlets

Remove Existing Traffic Signal

Remove Existing Inlet

Construction Limits

MATCH LINE STA 86+00

KGE MH. See note 1 Sheet CV 1.1

Remove Existing Inlet

Remove Existing Traffic Signal

Remove Existing Inlet

Remove 44 LF 21" RCP

Remove 18 LF 15" RCP

Remove 94 LF 15" RCP

Existing SW to Remain

BL Sta 83+80.04 14.45' Rt.* Install 1-Type 1A Curb Inlet MH Top=110.95 FL(NW)=107.69 FL(W)=107.79

BL Sta 83+48.55 Begin Removal and Reconstruction Sawcut & Match Exist. Pavement

BL Sta 27+68.89 41.81' Rt. Adjust MH Top=110.97 Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 28+10.29 37.00' Rt. Light Fixture

BL Sta 28+80.45 41.10' Rt. Adjust MH Top=111.36 Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 28+94.43 37.50' Rt. Light Fixture

BL Sta 29+84.89 38.10' Rt. Light Fixture

Construct 29' Concrete Drive Approach (Sheet CV 4.9) 230 S.F. 8" Reinf. Conc.

BL Sta 29+44.89 38.10' Rt. Light Fixture

BL Sta 29+76.10 38.10' Rt. Light Fixture

BL Sta 26+23.60 Type 2 Curb Inlet MH Top=111.59 FL(N)=108.33 FL 4" Stub (N)=108.59

BL Sta 27+05.77 40.19' Rt. Existing KGE MH No Adjustment Required Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 26+56.15 38.10' Rt. Light Fixture

BL Sta 25+73.86 41.19' Rt. Adjust MH Top=111.87 Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 25+76.10 38.10' Rt. Light Fixture

BL Sta 26+87.40 37.69' Lt. Light Fixture

BL Sta 26+92.94 Lt. 1-6" RCMH Top=111.57 FL(NE)=105.36 FL(W)=105.56 FL(SE)=106.96

BL Sta 27+70.99 Douglas= Sta 85+00.00 Sycamore

BL Sta 27+63.94 3.74' Lt. Radius Point

Remove Existing Inlet Plug Pipe (N)

Remove 65 LF 24" RCP

40' R/W

Relocate Pole (by others)

80 S.F. 5'x4" Sidewalk

Remove Existing Inlets

Remove Existing Traffic Signal

Remove Existing Inlet

Construction Limits

MATCH LINE STA 86+00

KGE MH. See note 1 Sheet CV 1.1

Remove Existing Inlet

Remove Existing Traffic Signal

Remove Existing Inlet

Remove 44 LF 21" RCP

Remove 18 LF 15" RCP

Remove 94 LF 15" RCP

Existing SW to Remain

BL Sta 83+80.04 14.45' Rt.* Install 1-Type 1A Curb Inlet MH Top=110.95 FL(NW)=107.69 FL(W)=107.79

BL Sta 83+48.55 Begin Removal and Reconstruction Sawcut & Match Exist. Pavement

BL Sta 27+68.89 41.81' Rt. Adjust MH Top=110.97 Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 28+10.29 37.00' Rt. Light Fixture

BL Sta 28+80.45 41.10' Rt. Adjust MH Top=111.36 Replace KGE MH Lid w/ City of Wichita MH Lid

BL Sta 28+94.43 37.50' Rt. Light Fixture

BL Sta 29+84.89 38.10' Rt. Light Fixture

Construct 29' Concrete Drive Approach (Sheet CV 4.9) 230 S.F. 8" Reinf. Conc.

BL Sta 29+44.89 38.10' Rt. Light Fixture

BL Sta 29+76.10 38.10' Rt. Light Fixture

BL Sta 26+23.60 Type 2 Curb Inlet MH Top=111.59 FL(N)=108.33 FL 4" Stub (N)=108.59