


CONSTRUCTION NOTES

- ① CONSTRUCT AC PAVEMENT 7" (5" BIT BASE) WITH CRUSHED ROCK BASE 8", REINFORCED
- ② CONSTRUCT CONCRETE CURB & GUTTER, COMBINATION TYPE 1 (6" & 1-1/2")
- ⑤ CONSTRUCT AC PAVEMENT 7" (5" CONCRETE BASE*) WITH CRUSHED ROCK BASE 8", REINFORCED
- ⑥ CONSTRUCT CONCRETE SIDEWALK, 4" (6' WIDE)
- ⑦ SAW CUT & MATCH EXISTING PAVEMENT (24' NORTH OF SECTION LINE)

NOTES

*CONSTRUCT REINFORCED CONCRETE BASE WHEN THE WIDTH OF ASPHALT IS LESS THAN 6'. TRANSVERSE JOINTS SHOULD BE SPACED NO MORE THAN 12'. THE ASPHALT SURFACE SHALL BE SAWS AND SEALED ALONG THE LONGITUDINAL JOINT OF THE PAVEMENT WIDENING AND THE TRANSVERSE JOINTS IN THE CONCRETE BASE.

PRELIMINARY PLAN. NOT FOR CONSTRUCTION.
 This document is preliminary in nature and is not a final, signed and sealed document.



BAUGHMAN COMPANY
 315 Ellis St.
 Wichita, KS 67211
 316-262-7271
 BaughmanCo.com

13TH STREET WIDENING

PAVING PLAN

CIP IMPROVEMENTS

PROJECT NUMBER:
 472-2020-085654

DESIGN: LP DRAWN: LP
 DATE: Apr. 8, 2021

SHEET **8** OF **32**