

SUMMARY OF PAVEMENT MARKINGS															
LOCATION	100 mm Solid White Edge Line	150 mm Broken White Lane Line	150 mm Dotted White Extension Line	150 mm Solid White Lane Line	200 mm Solid White Core Line	300 mm Solid White Diagonal Line	300 mm Solid White Chevron Line	300 mm Solid White Type I Crosswalk Line	600 mm Solid White Type II Crosswalk Line	600 mm Solid White Stop Line	100 mm Solid Yellow Edge Line	100 mm Solid Yellow Double Line	100 mm Solid Yellow Line	100 mm Broken Yellow Line	300 mm Solid Yellow Diagonal Line
PARTICIPATING		222.0		144.0			144.0		44.0		1,292.0	98.0			52.0
NON-PARTICIPATING		99.0										236.0			
TOTALS		321.0		144.0			144.0		44.0		1,292.0	334.0			52.0

SUMMARY OF WORD & SYMBOL MARKINGS											
LOCATION	RIGHT TURN	LEFT TURN	STRAIGHT	RIGHT TURN	LEFT TURN	NO LEFT TURN	STOP	ONLY	X-ING	SCHOOL	
TOTALS											

NOTE: For specific pavement marking details and dimensions see plan sheets

NOTE: ALL TOTALS REFLECT ACTUAL QUANTITY OF PAVEMENT MARKING MATERIALS REQUIRED.

RECAPITULATION OF QUANTITIES			
ITEMS	(A)	(B)	TOTAL
PAVEMENT MARKING (COLD PLASTIC)(WHITE)(100 mm)			m
PAVEMENT MARKING (COLD PLASTIC)(WHITE)(150 mm)			m
PAVEMENT MARKING (COLD PLASTIC)(WHITE)(200 mm)			m
PAVEMENT MARKING (COLD PLASTIC)(WHITE)(300 mm)			m
PAVEMENT MARKING (COLD PLASTIC)(WHITE)(600 mm)			m
PAVEMENT MARKING (COLD PLASTIC)(YELLOW)(100 mm)			m
PAVEMENT MARKING (COLD PLASTIC)(YELLOW)(300 mm)			m
PAVEMENT MARKING SYMBOL (COLD PLASTIC)(WHITE)(		)	EACH
PAVEMENT MARKING SYMBOL (COLD PLASTIC)(WHITE)(		)	EACH
PAVEMENT MARKING SYMBOL (COLD PLASTIC)(WHITE)(		)	EACH
PAVEMENT MARKING SYMBOL (COLD PLASTIC)(WHITE)(		)	EACH
PAVEMENT MARKING (PATTERNED COLD PLASTIC)(WHITE)(100 mm)			m
PAVEMENT MARKING (PATTERNED COLD PLASTIC)(WHITE)(150 mm)	36.0	99.0	465.0
PAVEMENT MARKING (PATTERNED COLD PLASTIC)(WHITE)(200 mm)			m
PAVEMENT MARKING (PATTERNED COLD PLASTIC)(WHITE)(300 mm)	144.0		144.0
PAVEMENT MARKING (PATTERNED COLD PLASTIC)(WHITE)(600 mm)	44.0		44.0
PAVEMENT MARKING (PATTERNED COLD PLASTIC)(YELLOW)(100 mm)	1,292.0	236.0	1,628.0
PAVEMENT MARKING (PATTERNED COLD PLASTIC)(YELLOW)(300 mm)	52.0		52.0
PAVEMENT MARKING SYMBOL (PATTERNED COLD PLASTIC)(WHITE)(		)	EACH
PAVEMENT MARKING SYMBOL (PATTERNED COLD PLASTIC)(WHITE)(		)	EACH
PAVEMENT MARKING SYMBOL (PATTERNED COLD PLASTIC)(WHITE)(		)	EACH
PAVEMENT MARKING SYMBOL (PATTERNED COLD PLASTIC)(WHITE)(		)	EACH
PAVEMENT MARKING (HIGH DURABILITY)(WHITE)(300 mm)			m
PAVEMENT MARKING (HIGH DURABILITY)(WHITE)(600 mm)			m
PAVEMENT MARKING SYMBOL (HIGH DURABILITY)(WHITE)(		)	EACH
PAVEMENT MARKING SYMBOL (HIGH DURABILITY)(WHITE)(		)	EACH
PAVEMENT MARKING SYMBOL (HIGH DURABILITY)(WHITE)(		)	EACH
PAVEMENT MARKING SYMBOL (HIGH DURABILITY)(WHITE)(		)	EACH
PAVEMENT MARKING (FOIL BACKED)(WHITE)(100 mm)			m
PAVEMENT MARKING (FOIL BACKED)(WHITE)(200 mm)			m
PAVEMENT MARKING (FOIL BACKED)(WHITE)(300 mm)			m
PAVEMENT MARKING (FOIL BACKED)(YELLOW)(100 mm)			m
PAVEMENT MARKING (FOIL BACKED)(YELLOW)(300 mm)			m
PAVEMENT MARKING REMOVAL			m

(A) PARTICIPATING

(B) NON-PARTICIPATING

NOTE:

WORDS & SYMBOLS SHALL CONFORM TO THE LATEST EDITION OF "STANDARD ALPHABETS FOR HIGHWAY SIGNS AND PAVEMENT MARKINGS" PRINTED BY THE U.S. DEPARTMENT OF TRANSPORTATION, FEDERAL HIGHWAY ADMINISTRATION.

PRIOR TO COMMENCEMENT OF PAVEMENT MARKING WORK THE ENGINEER WILL ESTABLISH THE LIMITS FOR "NO PASSING" ZONES. THESE LIMITS SHALL BE USED FOR THE LOCATION OF "NO PASSING" LINES AND FOR THE COMPUTATION OF ACTUAL MARKING QUANTITIES FOR THIS LINE TYPE.