

ELASTOMERIC BEARING DEVICE

(36 Required)
(18 Each @ Pier #1 & #4)

SPECIAL BEARING PLATE NOTE:

Paint all exposed surfaces of the 1/2"x1'-4"x1'-10" plate with a shop coat of inorganic zinc paint. The stainless steel plates shall be an accurate flat surface and have a surface finish of 0.008 milli-inch root mean square (rms). Protect the surface from damage until beams are placed on the bearing device. All materials and labor for the special bearing plates shall be subsidiary to the bid item "Elastomeric Bearing".

GENERAL NOTES:

Bond the Bearing Pad to the concrete, at top of the seat, by use of an approved epoxy or bonding agent recommended by the manufacturer of the pad.

The bid item "Elastomeric Bearing" includes the reinforced elastomeric bearing pad.



SECTION B-B

(Transverse Section. See "Bearing Device Details I" for location.)

PREPARED BY
BG CONSULTANTS, GROUP INC.
727 NORTH WACO
SUITE 260
WICHITA, KANSAS 67203
PHONE: 316-352-9333

CONSULTANTS:

AMIDON AVE. BRIDGE
AT ARKANSAS RIVER

WICHITA, KANSAS

CITY OF WICHITA

REVISIONS:

MARK	DATE	DESCRIPTION

PROJ NO: E1010-4025062
SCALE:
DATE: 07/08/2022
DESIGNED BY: JBM
DRAWN BY: JBM
CHECKED BY: WBS

SHEET TITLE:

BEARING DEVICE
DETAILS III

SHEET NO.
46
SHEET 46 OF 128

bidtools
$DATE$ - $TIME$ - $FILE$

IF THIS DRAWING IS LESS THAN 22" X 36" IT IS A REDUCED SIZE DRAWING