CONCRETE DRIVE

SAW-CUT JOINT TO FOLLOW RADIUS

20'-0" | 20'-0" | 20'-0" | 20'-0" | 20'-0" | 20'-0"

5'-0" | 5'-0" TYP.

6'-0"

2'-6"

EQUAL | EQUAL

H-10-F | H-10-F | H-10-A | H-10-B | H-10-C | H-10-H | H-10-A | H-10-A | H-10-B | H-10-C | H-10-A | H-10-B

W-3-F | W-3-F | W-3-F | W-3-F | W-3-F | W-3-F

W-3-C | W-3-C | W-3-C | W-3-C

CONCRETE SIDEWALK (TYPICAL)

STONE WALL (TYPICAL)

2'-0"

5'-0" TYP.

50'-0"

45'-0"

45'-0"

45'-0"

45'-0"

8'-0"

4'-0"

CHARCOAL CONCRETE PAVERS - TYPICAL

64'-0" R.

64'-0" R.

7'-0"

18'-0"

10'-0"

90°

SURVEY POINT 205

19'-0"

64'-0" R.

PRECAST CONCRETE PAVERS LAID IN A HERRINGBONE PATTERN @ 45° TO ROADWAY ℄, TYPICAL

51+00 | 51+20 | 51+40

CONCRETE BAND

2'-0"

CONCRETE SIDEWALK (TYPICAL)

CONCRETE DRIVE

SAW-CUT JOINT TO FOLLOW RADIUS

BEIGE CONCRETE PAVERS (TYPICAL)

CHARCOAL CONCRETE PAVERS (TYPICAL)

16'-0"

16'-0" R.

16'-0"

50'-0"

EXPANSION JOINT (TYP.)

CONTROL JOINTS @ 6'-0" O.C., TYPICAL.

STONE WALL (TYPICAL)

CONCRETE SIDEWALK (TYPICAL)

6'-0"

5'-0" TYP.

2'-6"

MEET EXISTING SIDEWALK

3'-0" R.

2'-6"

5'-0" TYP.

8'-0" R.

6'-0"

NOTE: SEE SHEET H-1 FOR ADDITIONAL LAYOUT INFORMATION.

(A) ENLARGED PLAN

1/8" = 1'-0"

REV.	DATE	DESCRIPTION
△		
△		
△		
△		
△		

STATE OF KANSAS — MICHAEL E. SPRADING — No. 4400 — REGISTERED PROFESSIONAL ENGINEER

THE CITY OF WICHITA — SEDGWICK COUNTY, KANSAS

HELLMUTH, OBATA & KASSABAUM, INC.
DALLAS, TEXAS

PROFESSIONAL ENGINEERING CONSULTANTS, PA
WICHITA, KANSAS

BRAD J. GOLDBERG, ARTIST
DALLAS, TEXAS

DRAWN BY | APPROVED BY

MUSEUM DISTRICT
ROADWAY & PEDESTRIAN IMPROVEMENTS
CITY OF WICHITA, KANSAS

SHEET TITLE:
HARDSCAPE PLAN

PROJECT NO.	ISSUE DATE	SCALE	SHEET
92-036-122	11 JULY 1997	1/8"=1'-0"	H-7